MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

NAVAL POSTGRADUATE SCHOOL
Monterey, California

DTIC
ELECTE
MAY 8 1984

D

A

THESIS

HEAT TRANSFER MEASUREMENTS OF
INTERNALLY FINNED ROTATING HEAT PIPES

by

Adnan Nefesoglu

December 1983

Thesis Advisor: P. J. Marto

Approved for public release; distribution unlimited.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. A140 847	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Heat Transfer Measurements of Internally Finned Rotating Heat Pipes		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis December 1983
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Adnan Nefesoglu		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93943		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93943		12. REPORT DATE December 1983
		13. NUMBER OF PAGES 102
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Condenser, Enhancement, Condensation, Noncondensable Gases, Rotating Heat Pipe, Performance, Helical and Straight Fin, Internal Heat Transfer Coefficient.

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

A rotating cylindrical heat pipe was tested using various internally finned condensers and was compared with a smooth-wall cylinder. Each condenser was tested at rotational speeds of 700, 1400 and 2800 rpm with film condensation. Distilled water was used as the working fluid.

The heat transfer rate of each condenser was plotted versus the driving temperature difference between the vapor saturation

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73
S/N 0102-LF-014-6601

temperature and the cooling water inlet temperature. The objective of this investigation was to study the performance with various fin configurations and to find an optimum fin geometry.

As expected, in all cases, performance was improved with increasing rpm. The performance of internally finned condensers was found to be as much as 230 percent greater than that of the smooth condenser.

Heat Transfer Measurements
of Internally Finned Rotating Heat Pipes

by

Adnan Nefesoglu
Lieutenant J. G., Turkish Navy
Turkish Naval Academy, 1976

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN MECHANICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL
December 1983

Author: _____

Approved by: _____
                                    Thesis Advisor

_____
                                    Second Reader

_____
Chairman, Department of Mechanical Engineering

_____
          Dean of Science and Engineering

3

ABSTRACT

A rotating cylindrical heat pipe was tested using various internally finned condensers and was compared with a smooth-wall cylinder. Each condenser was tested at rotational speeds of 700, 1400 and 2800 rpm with film condensation. Distilled water was used as the working fluid.

The heat transfer rate of each condenser was plotted versus the driving temperature difference between the vapor saturation temperature and the cooling water inlet temperature. The objective of this investigation was to study the performance with various fin configurations and to find an optimum fin geometry.

As expected, in all cases, performance was improved with increasing rpm. The performance of internally finned condensers was found to be as much as 230 percent greater than that of the smooth condenser.

TABLE OF CONTENTS

6

LIST OF TABLES

LIST OF FIGURES

NOMENCLATURE

A_i inner surface area, m^2

C_p specific heat, kJ/kgK

D_o outside diameter, m

g acceleration of gravity $(\omega^2 r)$, m/s^2

h_f finned condenser internal heat-transfer coefficient, $W/m^2.K$

h_{fg} latent heat of vaporization, kJ/kg

h_i internal heat-transfer coefficient, $W/m^2.K$

h_o external heat-transfer coefficient, $W/m^2.K$

h_s smooth condenser internal heat transfer coefficient, $W/m^2.K$

k thermal conducivity, $W/m.K$

k_w wall thermal conductivity, $W/m.K$

L Length, m

$\dot{m}$ mass flow rate of coolant kg/s

Q heat-transfer rate from the condensing Vapor, W

Q_f frictional heat rate, W

Q_t the total heat-transfer rate from the cooling water, W

r_i inner radius, m

r_o outer radius, m

T_{ci} cooling water inlet temperature, Degrees C

T_{co} cooling water outlet temperature, Degrees C

T_f film temperature, Degrees C

T_{wi} inside wall temperature, Degrees C

T_{wo} outside wall temperature, Degrees C

ΔT temperature difference, $T_s - T_{w_i}$, Degrees C

M dynamic viscosity, kg/m.S

ω angular velocity, rad/s

ρ density of condensate, kg/m^3

σ surface tension, N/m.

ACKNOWLEDGMENT

I. INTRODUCTION

A. THE ROTATING HEAT PIPE

The rotating heat pipe is a device to transfer heat from a rotating heat source. This device basically consists of a cylindrical evaporator and condenser and a working fluid to transfer energy from one end to other (Figure 1.1).

During operation the heat pipe is rotated and the working fluid makes an annular shape in the evaporator section. Heat supplied to the evaporator vaporizes a portion of the working fluid, creating a pressure gradient from the evaporator to the opposite end.

To remove heat from the condenser, external cooling is applied to the condenser and the working fluid vapor condenses on the inner wall. Condensate flows back to the evaporator by the driving force of the pressure gradient resulting from the axial difference in the condensate film thickness along the condenser wall.

B. BACKGROUND

The first rotating heat pipe at the Naval Postgraduate School was designed and constructed by Daley [Ref. 1] in 1970. He used stainless steel for his truncated-cone condenser with a three-degree half angle. In 1971, Newton [Ref. 2] performed experiments with the basic

13

Figure 1.1 The Rotating Heat Pipe

system from Daley, using distilled water as the working fluid at rotational speeds of 700 and 1400 rpm. In 1972, Woodard [Ref. 3] continued by using the same basic system and the same working fluid at 700, 1400 and 2800 rpm. In the same year, Schaffer [Ref. 4] tested truncated copper condensers with different working fluids (alcohol, freon 113 and water). In 1974, Tucker [Ref. 5] examined dropwise condensation by coating the condenser inner wall with a silicone grease.

With all the system problems known up to 1976, Loynes [Ref. 6] redesigned the system parts and ran the experiment and obtained results similar to those of Tucker [Ref. 5]. Later in the same year, Wagenseil [Ref. 7] tested the same truncated cone with filmwise condensation. Further, he examined both smooth-walled and internally-finned cylindrical condenser sections. In 1977, Tantrakul [Ref. 8] obtained experimental data for 0.5-degree-cone-angle, truncated, cylindrical condensers with various working fluids (water, ethanol, freon 113). In 1979, Weigel [Ref. 9] tested smooth and internally-finned cylindrical condensers.

Four years later in 1983, Gardner [Ref. 10] brought the system b ck into operation. His objective was to examine variou c ... ical, internally-finned tubes. His attempts to take ... a were somewhat discouraging because of the presence of noncondensable gases in the system. Also, he

had problems with the thin (0.12-mm dia.) thermocouple wires he used and with the pin connectors. The small size of the wires and the rectangular shape of the connector caused detachment of the thermocouple wires at high rotational speeds because of the large centrifugal forces.

C. THESIS OBJECTIVES

Gardner [Ref. 10] recommended that the following modifications be made on the apparatus:

1. Fix vacuum leaks to avoid any in-leaks of noncondensable gas (air) into the system during operation.

2. Design a new, cylindrical strip terminal to replace the pin connectors to allow wall thermocouple calibration in a calibration bath and protect wires from breaking away at high rotational speeds.

3. Design a new cooling water mixing chamber for good mixing of water to minimize fluctuations of the cooling water outlet temperature.

Following the above-mentioned modifications, the primary objectives of this thesis were:

1. To produce experimental results for a smooth cylindrical pipe and compare with Wagenseil's data for one-inch-diameter smooth pipe. In addition to this comparison, these data are used to provide a basis for the evaluation of various internally-finned pipes.

16

2. To use commercially-available, cylindrical, condensers which are internally finned (both straight and helical fins) to find the optimum fin geometry (i.e., fin density, helix angle, and relative fin size such as fin height/condenser diameter).

II. EXPERIMENTAL EQUIPMENT

A. DESCRIPTION OF EQUIPMENT

The experimental apparatus is shown in Figure 2.1.
Figure 2.2 shows a cross-sectional view of the heat pipe,
while Figure 2.3 shows a schematic of the apparatus. The
entire system is bolted to a steel bed-plate which can be
oriented from horizontal to a near-vertical position.

1. Evaporator

The evaporator (Figure 2.1) is a copper cylinder
with o-ring seals at each end. The dimensions are 100mm
in diameter and 70mm in length.

2. Heater

The heater (Figure 2.1) is a chromel - a wire with
magnesium oxide insulation in an inconel sheath. Savereisen
insulation is placed over the heater followed by a quilted
insulating pad taped around the heater, and wrapped around
with 6mm-wide, woven, nylon tape. This thermal insulation
was secured in three places by wires. Electrical power to
the rotating heater is supplied through four pairs of
carbon brushes riding on a pair of bronze collector rings.
The resistance of heater is 1.8 ohms at the collector rings.

3. Power Supply

A single-phase, 440-volt, 60-Hz line voltage,
regulated by a voltage sensing circuit, was used to

ROTAMETER

OIL DRIPPER

INLET MIXING BOX

COOLING CHAMBER

SLIP RING

EVAPORATOR

DRIVE MOTOR

Figure 2.1 Photograph of the Rotating Heat Pipe System

19

Figure 2.2 Cross-Sectional Drawing of the Rotating Heat Pipe

CYLINDRICAL THERMOCOUPLE
JUNCTION BOARD

VENT

SLIP-RING COUPLING

VITON O-RING

CONDENSER

THERMOCOUPLE WELLS

EVAPORATOR

HEATER

VITON O-RING

VIEWPORTS

COLLECTOR RINGS

provide power to the heater. This line voltage was fed
into a differential voltage attenuator that divided it by
one hundred. This divided voltage then passed through
a true-mean-square (TRMS) converter with an integration
period of 1ms. The output of TRMS converter was controlled
by a potentiometer on the control panel. The comparator
output was fed to the control input of a Holmar silicon
rectifier, which supplied amplified voltage to the collector
rings.

4. View Windows

Two 88.9mm diameter, 6.35mm-thick, pyrex glass
windows were mounted on the evaporator. The two glasses
were separated by 2mm by placing two gaskets between them.
The air gap between the two glasses minimized fogging on
the inner glass for easy observation during operation.

5. Bearings

The heat pipe was supported by two bearings. The
main bearing was externally cooled by water, and was
lubricated by an oil dripper. The drive-pulley bearing was
a self-lubricated, sealed bearing.

During the process of this work, the mounting of
the main bearing was unchanged, and Gardner's [Ref. 10]
method was used.

Figure 2.3   Schematic Diagram of the Rotating Heat Pipe System

6. Cooling System

As shown in Figure 2.3, the condenser was cooled by a spray of filtered-and-softened tap water. Cooling water sprayed along the condenser from four tubes placed at 90 degrees apart around the condenser. Sprayed water drained through two holes at the bottom of the cooling box into the mixing chamber. The cooling water temperatures were read by a single thermocouple at the inlet, and by five parallel thermocouples at the mixing-chamber outlet, respectively. Since the previous mixing chamber caused large temperature variations (up to $\pm$ 1.1 K), a new mixing chamber was designed (see Figure 2.3). This chamber provided more acceptable temperature fluctuations ($\pm$ 0.2 K). The cooling water flow rate was measured by a calibrated rotameter.

7. Condenser

During this work, the condensers built by Gardner [Ref. 10] were used. As an important modification, the drive-end flange was rebuilt as recommended by Gardner to eliminate one of the improperly placed o-rings (Figure 2.2).

Five copper test condensers were tested for this thesis. Each condenser was 295mm long with an effective length of 250mm. Spray cooling was provided only over the effective length.

23

As a basis for all different inside geometries, a smooth pipe was used with the following dimensions:

outer diameter   :   26.6mm

inner diameter   :   22.9mm

These pipe dimensions are the same as that used by Wagenseil [Ref. 7] and Gardner [Ref. 10] for their comparison purposes.

The other four finned condensers contained either straight or helical fins which were provided by Noranda Metal Industries of Newton, Connecticut.

1. Straight 22-fin condenser (Figure 2.4).

2. Helical 16-fin condenser which was tested by Weigel [Ref. 9] (Figure 2.5).

3. Helical 14-fin condenser (Figure 2.6).

4. Helical 36-fin condenser (Figure 2.6).

Specifications of these internally finned condensers are listed in Table (2.1).

8. System Drive and RPM Counter

The heat pipe was rotated by a variable-speed electric motor. A v-belt provided between the motor pulley and the pulley on the heat-pipe axis drove the system. Rotational speed was measured by a digital frequency counter attached to the system through a gear. Speed controller it had an accuracy of $\pm$ 1 rpm.

24

Figure 2.4 Photograph of a Section of the 22 Straight Fin Condenser

Figure 2-5 Photograph of a Section of the Helical 16-Fin Condenser.

Figure 2.6 Photograph of a Section of the Helical 14 Fin Condenser

27

Figure 2-7   Photograph of a Section of the Helical   36 Fin   Condenser

28

TABLE 1.1 SPECIFICATIONS OF THE INTERNALLY FINNED TUBES:

Finning	Number of Fins (mm)	Outside Diameter (mm)	Inside Diameter (mm)	Fin Height (mm)	Fin Thickness (mm)	Helix Angle (degree)	Area Ratios (Comparing to the smooth tube):		
							Outer	Inner (w/o fins)	Inner (with fins)
Straight	22	28.6	25.8	1.35	1.2	0	1.075	1.126	1.437
Helical	16	26.7	24.7	1.80	0.75	26.8	1.003	1.078	1.378
Helical	14	26.5	23.9	2.15	0.75	27.6	0.994	1.043	1.342
Helical	36	25.4	23.8	0.85	0.45	27.0	0.954	1.039	1.200

29

9. Vacuum and Pressure Test System

Since the experiments were performed under vacuum conditions, any inleakage of noncondensable gases (air) were a serious problem, as also discussed by Gardner [Ref. 10]. Therefore, considerable efforts were made to ensure vacuum-tightness of the system. Vacuum and pressure test lines, shown in Figure 2.8, were used to check for possible leaks. An aluminum test flange was installed in place of the glass view windows. The system was first pressure tested (to about 20psig) with nitrogen. The soap-bubble test was used to locate leaks. After fixing leaks found by the pressure test, a vacuum-hold test was performed over a period of about 10 hours. The system was accepted to be leak-free if the vacuum-lost rate was less than 0.1mm/hr.

For this work, two more test flanges were built to be able to test the evaporator and condenser sections separately. A proper fitting was installed to test the driving-end condenser flange o-ring.

B. INSTRUMENTATION

All temperatures were measured by 30-gage, type-E, teflon- and plastic-coated thermocouple wire. These thermocouples were calibrated using the procedures explained in Appendix B.

30.

Figure 2.8   Vacuum and Pressure Test System

After making sure that the condenser body and all the silver-soldered connections were air tight, the thermocouples were mounted within axial grooves on the outer surface using the following procedure:

First, the thermocouples were placed in grooves. The grooves were then filled with just sufficient amount of Devcon, type-B epoxy. A greased thin brass sheet was placed over the epoxy and held in place by a strong tape to anchor the thermocouple and epoxy in place. Four hours later these metal sheets were removed.

Vapor space thermocouples were inserted into the two vapor space thermocouple wells until they came in contact with the end of the well. All thermocouple wires were held to the condenser using wire wraps. The wires were passed through holdes in the flange at the drive end of the condenser, and were connected to the cylindrical thermocouple junction boards (Figure 2.9).

To protect wires from breaking apart from the junction board, due to centrifugal force at high rotational speeds, two layers of duct tape were used on the cylindrical junction board. This modification was quite satisfactory with no difficulties as reported by Gardner [Ref. 10] with the previous design.

The wall thermocouple and vapor thermocouple signals were transmitted from the system by a set of viscous, mercury slip rings.

32

Figure 2.9 Thermocouple Locations

33

The inlet and outlet temperatures of cooling water were also monitored by type-E thermocouples. The outlet thermocouple consisted of five separate thermocouples wired in parallel, and was inserted into the mixing box discharge line as shown in Figure 2.3.

The thermocouple voltages were read by a Hewlett-Packard (HP) 3054A, data acquisition system, and were entered to an HP-9826 computer. For data acquisition and analysis, a real-time, interactive program was used to reduce and store data on floppy disks [Appendix C].

Cooling water flow rate was measured with a standard rotameter. Accurate regulation of the flow rate was accomplished by adjusting the pressure regulator installed in the cooling line.

III. EXPERIMENTAL PROCEDURES

A. INSTALLATION AND TESTS

1. Inspect all o-rings and o-ring grooves to be sure they are clean and have no flaws.

2. Install the condenser without placing the cooling water box in position.

3. Install the test flange; connect a pressure source and raise the pressure inside the heat pipe to 0.3 MPa (43 psig). Wet the surfaces of all joints thoroughly with soap solution. Inspect all the joints and surfaces for leaks. If there are no leaks evident by the bubble test, follow the pressure gage on the system for 30 minutes. If any leaks are found, take appropriate corrective steps.

4. Disconnect the pressure source and install a vacuum test system. Evacuate the heat pipe, isolate the system and allow it to sit at least 6 hours. Monitor the vacuum in the system to ensure that there are no intolerable leaks.

5. After ensuring that there are no leaks on the condenser, take apart the condenser and install thermocouples.

6. Repeat steps 1-4, but this time place the cooling water box in position.

These tests will detect leaks that may allow non-condensable gases to be inducted into the heat pipe, which operates in a partial vacuum. Daniels and Williams [Ref. 14] have shown that noncondensable gases significantly reduce heat transfer rates in rotating heat pipes.

During the tests of this work, there were no o-ring leaks. But soldered joints produced several leaks which had to be re-soldered to ensure tightness.

B. PREPARATION OF THE HEAT PIPE INTERIOR

1. Remove test flange, tilt the evaporator end down a few degrees to allow the cleaning fluids to run off the heat pipe.

2. Using a brush, scrub the interior of the heat pipe with acetone. Rinse with water thoroughly.

3. Scrub the interior with ethyl alcohol, then rinse with distilled water.

4. Scrub the interior with a solution of equal parts of ethyl alcohol and 50 percent aqueous sodium hydroxide at 80 degrees Celsius. (CAUTION: THIS SOLUTION IS EXTREMELY IRRITANT WHEN CONTACTED BY SKIN. MAKE SURE TO WEAR PROPER EQUIPMENT.) Rinse with distilled water. Check the interior surfaces by spraying water to observe even wetting on the surface.

C. FILLING PROCEDURE

1. Tilt the slip-ring end down about 35 degrees.

2. Pour 300ml of distilled water into the pipe.

3. Dry the glass windows to avoid fogging between them.

4. Place the first glass window on the o-ring. Put the two spacer rings followed by the second window glass and one spacer ring.

5. Tighten the twelve view window retaining bolts consequentially. First, tighten every fifth bolt to 10 inch-lb torque. Then, repeating the procedure. This prevents the cracking of view windows during the installation and experiment.

D. VENTING PROCEDURE

1. Tilt the evaporator end down 30 degrees.

2. Remove the vent screw.

3. Set the power control to 14. Heat the system up to about 100 degrees C.

4. Turn on the data acquisition system and monitor the thermocouple outputs. This gives a chance to check all the thermocouples as the system is heating up. Monitor the vapor temperature (channels 40 and 49) and do not allow this temperature to increase higher than 106 degrees C (6400 μV).

5. When a steady steam flow is observed, out of the vent opening commence timing and allow venting for 10 minutes.

6. When venting is complete, install the vent screw with o-ring, and turn off power. Turn on the cooling water to cool the system off. Observe violent boiling in the system as it cools down.

E. RUNNING PROCEDURE

1. Bring the system to horizontal position using a level.

2. Wrap the thermocouple junction board with tape to protect the wires from breaking apart due to centrifugal forces.

3. Open the main bearing cooling water valve.

4. Open the needle valve on the oil dripper and adjust the oil flow to 2-3 drops per minute.

5. Open the condenser cooling water and adjust the flow to 40 percent.

6. Energize the computer and the data acquisition system. Load the program (RHPIPE).

7. Energize the frequency counter and set it for rpm display.

8. Pull the drive motor back and adjust for a proper V-belt tension. Rotate system by hand to ensure there is no binding.

9. Start the drive motor and bring the rpm to approximately
1100-1400 to obtain an annulus of water in the evaporator.
Then adjust the rpm to the level for this work, data were
taken at 700, 1400 and 2800 rpm.

10. Set the power control to a desired level. Monitor one
of the vapor space thermocouples; wait ten minutes for
system to reach steady-state temperatures. The criterion
for steady-state condition is when fluctuation is less than
± 4 microvolts for any EMF value.

[CAUTION: FOR SAFETY REASONS, DO NOT ALLOW THE VAPOR
TEMPERATURE TO EXCEED 106 DEGREE C (6400 μV).].

11. After steady state is reached, take 3 sets of data at
each power setting and average these values to reduce the
experimental uncertainties.

12. Hand plot heat flux vs. $(T_s - Tc_i)$ to follow data.

F. DATA REDUCTION

Data reduction and analysis are performed by HP 9826
computer using an interactive program written in Basic 2.
The original program written by Gardner [Ref. 9] was modified,
and a listing of this modified version (Program Name:RHPIPE)
is given in Appendix C. This program performs the following
steps:

1. Requests the entry of time, rpm, and cooling water
rotameter reading. Then samples each thermocouple EMF

twenty times and stores the raw data (mean values) on disk. File for future use.

2. In the analysis portion of the program, corrected temperatures, and in, the cooling water mass flow rate are calculated.

3. The program computes the heat transfer rate (Q) to this cooling water by the following energy balance equation:

$$Q = \dot{m} * C_p * (T_{\infty} - T_{ci}) - Q_f$$

where

Q = Heat transfer rate from condensing vapor [W]

$\dot{m}$ = Cooling water mass flow rate, [kg/s]

C_p = The specific heat of water, [kJ/kg-K]

T_{∞} = The cooling water outlet temperature, [Degree C]

T_{ci} = The cooling water inlet temperature, [Degree C]

Q_f = Frictional heat rate generated in the system by friction, when zero power applied. [W]

4. The program displays the following output neither short or long format. Short format is used to make a table or results. Long format displays all individual thermocouples which enables the user to check if all the thermocouples work properly:

Q	watts
$T_s - T_{c_i}$	degrees C
$T_s - T_{wall}$	degrees C
$T_{wall} - T_{avg}$	degrees C
$T_{co} - T_{ci}$	degrees C

6. The program stores the results on a disk file for future use.

IV. PRESENTATION AND DISCUSSION OF RESULTS

A. GENERAL COMMENTS

Five different condensers were tested for this thesis. To determine the heat transfer rate due to friction at the bearings, each condenser was tested at 700, 1400 and 2800 rpm with no power to the evaporator. The frictional heat transfer rate (Q_f) for each condition was calculated from the heat balance applied to cooling water.

Heat transfer rate (Q) versus the difference between saturation temperature and cooling water inlet temperature $(T_s - T_{ci})$, which is the driving potential temperature difference, were plotted. Data were taken incrementally for increasing and decreasing power settings.

Computer outputs for all runs are tabulated in Appendix C.

B. RESULTS OR SMOOTH WALL CONDENSER

Figure 4.1 and Tables C1, C2, and C3 show the results of the smooth wall condenser. This condenser was chosen to provide a base performance to compare to the internally finned condensers. As expected, data correlate well with the work of Wiegel [Ref. 9] and Wagenseil [Ref. 7].

The heat transfer rate shows the improvement with rpm. For a rotating cylinder, the condensate flow is induced by the pressure gradient established in the condensate as a

42

Figure 4.1 Smooth Condenser Thermal Performance

result of lts variable film thickness. Leppert and Nimmo
[Refs. 11 & 12] have shown, that for condensation on a flat
plate at a constant surface temperature:

$$Nu_T = 0.64 \ Sh_T^{1/5}$$

where

$$Sh_T = \frac{g\rho^2 h_{fg} \ L^3}{k\Delta T\mu}$$

For a rotating cylinder, the gravitational acceleration may
be replaced by the centrifugal acceleration, $\omega^2 r$. Roetzel
and Newman [Ref. 13] (for a rotating drum) recommended the
relation:

$$Nu_T = 0.78 \ Sh^{1/5}$$

These relationships show that the heat transfer rate on
the inside of a rotating cylinder increases with increasing
RPM, specifically;

$$Nu_T \ \alpha \ RPM^{2/5}$$

In a similar way, for constant heat flux, Nimmo and Leppert
[Refs. 11 and 12] also give;

$$Nu_q = 0.75 \ Sh^{1/4}$$

and Roetzel and Newman [Ref. 13] give:

$$Nu_q = 0.62 \ Sh^{1/4}$$

where

$$Sh_q = \frac{g\rho^2 h_{f_q} L^2}{\mu \dot{q}}$$

$$\dot{q} = \text{heat flux } (Q/A_i)$$

Therefore, in this situation

$$Nu_q \alpha RPM^{1/2}$$

In addition, the water-jet cooling on the outside of the condenser surface may, as an approximation, be treated in a similar way to steam condensation on a rotating cylinder. This problem was investigated by Nicol and Gacesa [Ref. 14]. They show that for high rotational speeds (i.e., Weber numbers greater than 500),

$$\frac{h_o D_o}{K} = 12.26 \ We^{0.496}$$

where

$$We = \rho \omega^2 D_o^3 / 4\sigma g$$

45

The outside heat-transfer coefficient is, therefore, proportional to the Weber number raised to 0.496 power so it is almost proportional directly to RPM.

Hence, with increasing rotational speeds both internal and external heat-transfer coefficients must increase.

To compare the theoretical and empirical results, Log-Log plots of the Nusselt versus Sherwood number were made as shown in Figures 4.2 and 4.3.

For this comparison, the following simplifications were made:

1. The condenser outside wall temperature was taken as the unweighted average of all thermocouple readings.

2. All fluid properties were evaluated at the film temperature.

$$T_f = \frac{T_s + \overline{T}_{wi}}{2}$$

where $\overline{T}_{wi}$ is the average inside wall temperature (K).

3. Heat flux through the condenser was considered uniform.

The average inside heat transfer coefficient was therefore

$$h_i = \frac{Q}{A_i [T_s - \overline{T}_{wi}]}$$

Figure 4.2 Sherwood Number vs. Nusselt Number for Constant Wall Temperature.

47

Figure 4.3 Sherwood Number vs. Nusselt Number for Constant Wall Heat Flux.

The mean Nusselt number, $Nu = \bar{h}_i L/k$ for a given heat
transfer rate was determined from the data and the Sherwood
number was calculated with the assumption of either
constant wall temperature or constant heat flux. Figures
4.2 and 4.3 show that, for a given set of data, as
$(T_s - \bar{T}_{wi})$ increases (i.e., Sh decreases), the Nusselt
number increases. This trend disagrees with empirical
equations, but agrees well with the data trend of
Wagenseil [Ref. 7] and Tantrakul [Ref. 8]. On the other
hand, the overall trend from one set of data to another
shows that the Nusselt number increases as Sherwood number
increases. The reason for this unusual discrepancy is
not known.

The condenser wall temperature profiles for the smooth
condenser are shown in Figure 4.4. This plot was made for
the values of wall temperature at the condition of
$(T_s - T_{ci}) = 70$ degrees C for all three RPM's. At all RPM's,
the temperature closest to the evaporator is a maximum.
This is caused by the heat conducted through the main
bearings (heat from the evaporator and the frictional
heat generated in the main bearing) if one neglects the
temperature at 5mm. From the evaporator end, the remaining
profiles are relatively flat to 130mm. And then they drop
off to a temperature close to that of the cooling water.

49

Figure 4.4 Wall Temperature Distribution of Smooth-Wall Condenser at 90 Degree C Saturation Temperature.

C. RESULTS OF THE STRAIGHT 22-FIN CONDENSERS

The heat transfer rates, determined for the 22-fin condenser at 700, 1400 and 2800 RPM are shown in Figure 4.5.

This condenser showed the best performance among the internally-finned condensers tested. These data show up to a 230 percent improvement over the data for the smooth-wall condenser.

In examining the geometrical properties of this finned tube (Table 2.1), notice that it has an area ratio (total inside area to smooth condenser inside area) of 1.437. Hence, the heat transfer improvement results are more than just due to the increase of surface area. Since the conditions on the outside of this condenser were almost identical to the smooth condenser case, then the observed increase in overall heat transfer must be due to a more significant increase in heat transfer on the inside.

D. RESULTS OF HELICAL 14 and 16 FIN CONDENSERS

The thermal performance of the helical 16-fin condenser is shown in Figure 4.6. At 2800 RPM, this condenser shows a 110 percent improvement over the smooth condenser. By helically finning the tube wall in addition to increasing the internal area, the counter-clockwise spiral acts as a condensate pump when the shaft is rotated in a clockwise fashion. The fins, therefore, act as impellers to force the condensate back to evaporator instead of relying upon

51

Figur 4.5   Straight 22-Fin   Condenser Thermal Performance

hyrostatic pressure. But this effect did not improve the performance as much as the straight fin condenser except for the 700 RPM case. Obviously, this pumping effect was not dominant at higher RPM. The reason for this unexpected phenomenon became clear when the interior surface of the spirally-finned condenser was examined. The surface between the fins is much rougher on the spirally-finned condenser then on the straight-finned condenser. Apparently, during fabrication of the helically-finned condenser, a series of transverse ridges are created in the trough region between fins, (Figure 2.5). These ridges do not appear in the straight finned condenser. As a result, the condensate undergoes more frictional resistance when flowing back to the evaporator. This extra resistance thicknes the film and reduces the heat transfer. Also, since the helical fins were thinner than the straight fins, they may not be as effective in condensing the vapor due to a lower fin efficiency.

The thermal performance of the helical 14-fin condenser (Figure 4.7) is almost identical to the results (Figure 4.6) of the 16-fin condenser with very similar fin geometry, helix angle and diameter.

E. RESULTS OF HELICAL 36-FIN CONDENSER

For this condenser, as shown in Figure 4.8, a thermal improvement of up to 40 percent over the smooth condenser

53

Figure 4.6 Helical 16-Fin Condenser Thermal Performance

8000
7000
6000
5000
4000
3000
2000
1000
0

Q (WATTS)

700 RPM
1400 RPM
2800 RPM
TYPICAL ERROR LIMIT

＊   0   +   ⌀

Ts-Tc1 (C)

0   10   20   30   40   50   60   70   80

Figure 4.7 Helical 14-Fin Condenser Thermal Performance.

Figure 4.8 Helical 36-Fin Condenser Thermal Performance.

56

is evident. This can be explained since the fin height
of this condenser is the smallest with 0.85mm. For this
case, the condensate thickness at the trough may cover a
large portion of the fin height, decreasing its effective-
ness for heat transfer since most of the condensation occurs
at the portion of the fin exposed to vapor. Due to this
reason, the improvement obtained on this condenser was
considerably smaller than for pipes with high fins.

F. INTERNAL HEAT TRANSFER ENHANCEMENT

The internal heat-transfer coeeficients of the
internally-finned and smooth condensers were calculated, by
using the following procedure:

The heat transfer rate Q may be written:

$$Q = \frac{T_s - \overline{T}_{wo}}{R_i + R_w}$$

so that the internal thermal resistance R_i is:

$$R_i = \frac{T_s - T_{wo}}{Q} - R_w \quad .$$

As a result, we may write:

$$\frac{1}{h_i A_1} = \frac{T_s - \overline{T}_{wo}}{Q} - \frac{\ln(r_o/r_i)}{2\pi L k_w} , \quad \text{or}$$

57

$$h_i = \left[A_i \left(\frac{T_s - \bar{T}_{wo}}{Q} - \frac{\ln(r_o/r_i)}{2\pi L k_w} \right) \right]^{-1}$$

where

A_i = Inside surface area, m^2 .

r_o = Outside radius , m .

r_i = Inside radius, m .

k_w = Thermal conductivity of wall, W/m.K .

(Assumed at 300 K for calculations.)

L = Effective length of condenser, m .

The internal heat transfer coefficient ratio of the internally finned to smooth wall condenser, (h_f/H_s) are ploted versus driving temperature difference $(T_s - T_{ci})$ in Figures 4.9 - 4.12. Figure 4.9 shows the variation for the straight 22 fin condenser while Figures 4.10, 4.11, and 4.12 show the plots of the helically finned condensers. Based upon the plots obtained, the following observations are made:

1. At low temperature differences, larger enhancements were observed due to very thin films on fins and in the troughs. As the temperature difference increases the films become thicker and this, of course, reduces the internal enhancement.

58

2.   The highest enhancement was observed for the straight
22-fin condenser with the highest area ratio (Figure 4.9).
Also, for the helical 36-fin condenser with the lowest area
ratio enhancement reaches the smallest level.

3.   In all the finned condensers, at low temperature
differences (where the enhancement is larger) the heat
transfer coefficient ratio improves when the rotational
speed is increased from 700 to 1400 rpm.   But the ratio
is somewhat less significant at 2800 rpm.

The reason for this is the expection of more flow
in the trough with increasing rpm.

At low rotational speeds, with lower flow rate, the
film thickness in the trough section will be smaller.   But
at very high rotational speeds, the thinner films on the
fin tips cause thicker films in the trough section.

But this phenomenon has to be further studied with
future experiments.   Using a finite element code to examine
the rpm effect on the internal heat-transfer coefficient
ratio will be an enlightening study.

Figure 4.9   Internal Enhancement of Straight Fin   Condenser

Figure 4.10   Internal Enhancement of Helical   16 Fin   Condenser

61

Figure 4.11   Internal Enhancement of Helical   14 Fin   Condenser

62

Figure 4.12 Internal Enhancement Of Helical 36 Fin Condenser

63

Figure 4.13   Variation of Film Thickness with RPM

V. CONCLUSIONS AND RECOMMENDATIONS

A. CONCLUSIONS

The following conclusions have been made based on the experimental results obtained:

1. At 2800 rpm, $T_s - T_{ci} = 30$ degree C,

   a. Helical 14 and 16 fin condenser performance improved by 110 percent.

   b. Straight 22 fin condenser provided the best performance improvement with 230 percent.

2. At 700 rpm, the heat-transfer-performance improvement for helical 14 and 16 fin and the straight fin performance increased as much as 225 percent.

3. Length of trough section and fin height play and important role on condenser performance. Condensers with small fin height, fin thickness, and with small trough section don't improve the performance significantly even though the number of fins is increased.

4. As rotational speed increases, internal and external heat transfer coefficients increase.

5. Internal heat-transfer-coefficient ratio of internally-finned condenser versus smooth wall condenser varies from 2 up to 20 depending on $(T_s - T_{ci})$ and rpm.

B. RECOMMENDATIONS

The following possible areas for future research should be considered.

1. Test additional helical and straight finned condensers to find the optimum fin geometry.

2. Develop computer code for cylindrical internally finned condenser and compare results to theory.

3. Test different diameter smooth tubes to find optimum dimensions for agreement of theory predicted by Nimmo and Leppert [Refs. 11 and 12], and Roetzel [Ref. 13].

4. Perform further study to examine the effect of rpm on internal heat transfer coefficient ratio. Examine the variation of this ratio by using finite element method.

5. The condensers which show the best thermal performance should be run for a prolonged period to test long-term endurance of performance.

APPENDIX A

UNCERTAINTY ANALYSIS

The uncertainty analysis was done by the method of Kline and McClintock [Ref. 15].

The following equations are used for data analysis.

$$\Delta T = T_{co} - T_{ci}$$

$$\Delta T_f = T_{co} - T_{ci}$$

$$Q_t = \dot{m}\, C_p\, \Delta T$$

$$Q_f = \dot{m}\, C_p\, \Delta T_f$$

$$Q = Q_t - Q_f$$

The uncertainties of the variables: Wq, Wq_t, Wq_f, Wc_p, Wm, Wt_i, Wt_o, Wt and Wt_f and the uncertainties:

$$Wt = \left[(Wt_o)^2 + (Wt_i)^2 \right]^{1/2}$$

$$Wt_f = \left[(Wt_o)^2 + (Wt_i)^2 \right]^{1/2}$$

$$\frac{Wq_t}{Q_t} = \left[\frac{Wm}{\dot{m}}^2 + \frac{Wc_p}{C_p}^2 + \frac{Wt}{\Delta T}^2 \right]^{1/2}$$

67

$$\frac{Wq_f}{Q_f} = \left[\left(\frac{Wm}{\dot{m}}\right)^2 + \left(\frac{Wc_p}{C_p}\right)^2 + \left(\frac{Wt_f}{\Delta T_f}\right)^2 \right]^{1/2}$$

$$Wq = \left[(Wq_t)^2 + (Wq_f)^2 \right]^{1/2}$$

The following data and uncertainties were for 2800 rpm, smooth wall condenser:

	Zero Power	Power On
c_p (kJ/kg-c)	4178	4178
W_{cp}	$\pm$ 1	$\pm$ 1
$\dot{m}$ (kg/sec)	0.1745	0.1745
Wm	$\pm$ 0.005	$\pm$ 0.005
T_{ci} (C)	20.71	20.69
Wt_{ci}	$\pm$ 0.05	$\pm$ 0.1
T_{co}	21.03	27.66
Wt_{co}	$\pm$ 0.05	$\pm$ 0.1

Uncertainty for the zero power ΔT_f :

$$W_{tf} = \left[(0.05)^2 + (0.05)^2 \right]^{1/2}$$

$$W_{tf} = \pm \ 0.07 \text{ degree C}$$

Uncertainty for the ΔT :

$$W_t = [(0.1)^2 + (0.1)^2]^{1/2}$$

$$W_t = \pm 0.14$$

Uncertainty for frictional heat transfer rate, Q_f

$$Q_f = (0.1745)(4178)(21.03 - 20.71)$$

$$Q_f = 233.3 \text{ watts.}$$

$$W_{qf} = 233.3 \left[\left(\frac{0.005}{0.1745}\right)^2 + \left(4178\right)^2 + \left(\frac{0.07}{0.32}\right)^2 \right]^{1/2}$$

$$W_{qf} = \pm 51.47 \text{ watts.}$$

The uncertainty for total heat transfer rate, Q_t.

$$Q_t = (0.1745)(4178)(27.66 - 20.69)$$

$$Q_t = 5081.1 \text{ watts.}$$

$$W_{qt} = 5081.1 \left[\left(\frac{0.005}{0.1745}\right)^2 + \left(\frac{1}{4178}\right)^2 + \left(\frac{0.17}{6.97}\right)^2 \right]^{1/2}$$

$$W_{qt} = \pm 177.2 \text{ watts.}$$

69

Heat-transfer rate from vapor and its uncertainty:

$$Q = 5081.1 - 233.3$$

$$Q = 4847.8$$

$$W_q = [(177.2)^2 + (51.47)^2]$$

$$W_q = \pm\ 184.5 \ \text{watts.}$$

APPENDIX B

CALIBRATION

A. ROTAMETER CALIBRATION

The rotameter was calibrated for volume flow rate in cubic meters per second by the following procedure. The water flow was directed into a tank placed on a scale. The temperature was measured and the density of water was calculated from subcooled liquid tables. The flow rate was brought to the desired rotameter reading and the time required to add .20 lbm to the tank was measured. Mass flow rate was calculated by taking mass-time ratio and converted to volume flow rate. A plot of volume flow rate versus rotameter reading was made and a linear calibration curve was derived by using least square feet of the data. The equations for volume flow rate as a function rotameter reading and water density as a function of temperature were incorporated into the data acquisition and analysis program.

B. THERMOCOUPLE CALIBRATION

All thermocouple were calibrated by immersing them into a Rosemount Model 913A calibration bath and using a mercury-in-glass thermometer (accuracy $\pm$ .028 degree c) as a standard.

71

1. Cooling Water Thermocouples

One cooling water inlet and five outlets (in parallel) thermocouples were inserted into the bath. The bath temperature was varied up and down with 10 degree increments from 10 to 50 degrees C. At each data point, the actual temperature measured by thermometer and the temperature measured by the data acquisition system were recorded. A plot of bath temperature minus measured temperature by thermocouples ($T_{bath} - T_{tc}$) versus thermocouple temperature (T_{tc}) was made and a linear calibration curve derived. The calibration equations for T_{co} and T_{ci} were incorporated into the data acquisition system. Figures B.1 and B.2 show the calibration curves for (channel 50) cooling water inlet and (channel 51) cooling water outlet temperature calibration curves.

2. Condenser Wall and Vapor Space Thermocouples

The same procedure as described above was followed for wall and vapor space thermocouple calibration.

Following steps were done:

a. The smooth wall condenser thermocouples were calibrated without installing on the wall. A calibration curve was derived.

b. The smooth wall condenser thermocouples were then installed on the wall and calibrated again. Agreement between the two curves was observed. First calibration curve is used for smooth wall condenser temperature calibration.

72

Figure B.1 Cooling Water Inlet Temperature Thermocouple Calibration
Curve

73

Figure B.2 Cooling Water Outlet Temperature Thermocouple Calibration
Curve

74

c. Helical 16-fin condenser wall thermocouples were installed and calibrated. Derived calibration curve was compared to smooth wall condenser curve (Figure B.3) and disagreement went up to 0.04 degree C. Since, disagreement was reasonable, the smooth wall condenser thermocouple calibration curve was used.

d. Helical 14 and 36 fin condenser wall temperature thermocouples were calibrated and compared to the smooth wall condenser calibration curve. Maximum disagreement was 0.2 degree C. (Figures B.4 and B.5).

2. Since the diagreement of wall thermocouples was less than 0.2 degrees C for all examined cases, the other condenser wall thermocouples were not calibrated and for all the condensers the same calibration curve, which was derived for the smooth wall condenser, was used.

Figure B.3 Helical 16 Fin Condenser Wall Thermocouples Calibration
Curve (Smooth Condenser Curve Plotted for Comparision)

Figure B.4   Helical   14 Fin   Condenser Calibration

77

Figure B.5 Helical 36 Fin Condenser Calibration

78

APPENDIX C

DATA ACQUISITION AND ANALYSIS PROGRAM AND TABULATED RESULTS

```
1000! ----------------------------------------------------------
1010! FILE NAME: RHPIPE
1020! REVISED:   October 17, 1983
1030! ----------------------------------------------------------
1040!
1050! This program is designed for use with the HP
1060! computer and the HP3054A data acquisition system
1070! to do the following:
1080!   1. Gather data from the ROTATING HEAT PIPE and
1090!      store these data on disk
1100!   2. Reduce the data, display the heat pipe heat flux
1110!   3. Store results on disk for later plotting
1120!
1130! The following variables are used in this program:
1140! Roto       Rotameter reading
1150! Mf         Cooling water mass flow (kg/s)
1160! Rpm        Rotor speed (rev/min)
1170! Cp         Average specific heat of cooling water
1180!            (J/kg-K)
1190! Emf(I)     Array containing the thermocouple voltages
1200! Tci        Cooling water inlet temperature (C)
1210! Tco        Cooling water outlet temperature (C)
1220! Ts         Vapor space temperature (C)
1230! Twall      Average heat pipe outside wall temp (C)
1240! Tavg       Average cooling water temp (C)
1250! Del_t      Ts-Tci, used in one of the plots
1260! Del_t2     Ts-Twall
1270! Del_t3     Twall-Tavg
1280! Q          Heat transfer rate (W)
1290! Qf         Heat generated by bearing friction (W)
1300! T(I)       Temperatures
1310! Aa(0)      Inner surface area of smooth pipe (m^2)
1320! Aa(1)      Inner surface area of 16 spiral fin pipe (m^2)
1330! Aa(2)      Inner surface area of 14 spiral fin pipe (m^2)
1340! Aa(3)      Inner surface area of 32 spiral fin pipe (m^2)
1350! Aa(4)      Inner surface area of 22 straight fin pipe (m^2)
1360! Ar         Area ratio: AN/AO
1370! Uo         Overall heat-transfer coefficient of
1380!            smooth pipe (W/m^2-K)
1390! Ua         Overall heat-transfer coefficient of
1400!            finned pipe (W/m^2-K)
1410! Roh        Density of cooling water (kg/m^3)
1420!
1430   DIM Emf(11),T(11),A(9),Aa(4)
1440   DATA .104967248,17189.45282,-282639.085,12695339.5,-448703084.6,1.10866E10
1450   DATA -1.76807E11,1.1842E12,-9.19278E12,2.06132E13
1460   READ A(*)  !   reads in coefficients for type-E thermocouple equation
1470   PRINTER IS 701
1480   DATA 10,11,12,13,14
1490   READ Aa(*)
1500   BEEP
1510   INPUT "ENTER MONTH, DATE AND TIME (MM:DD:HH:MM:SS)",Date$
1520   OUTPUT 709:"TD":Date$
1530   BEEP
1540   INPUT "ENTER PIPE CODE",Code
1550   Area=Aa(Code)
```

```
1560   J=0       ! this is a counter used if data are being retrieved from disk fil
e
1570   Jj=0      ! this is a counter used to control the printing of the temperatur
es
1580   BEEP
1590   INPUT "ENTER INPUT MODE (1=3054A,2=FILE)",Im
1600   IF Im=1 THEN
1610   BEEP
1620   INPUT "GIVE A NAME FOR THE NEW DATA FILE",D_file$
1630   CREATE BDAT D_file$,40
1640   ELSE
1650   BEEP
1660   INPUT "GIVE THE NAME OF OLD DATA FILE",D_file$
1670   BEEP
1680   INPUT "ENTER # OF DATA RUNS STORED",Nrun
1690   END IF
1700   BEEP
1710   INPUT "GIVE OUTPUT VERSION (1=SHORT,2=LONG)",Iov
1720   ASSIGN @File TO D_file$
1730 !
1740 ! Gather data
1750 !
1760 ! This section will take twenty readings foreach thermocouple and average
1770 ! them.  This is done to reduce data scattering.  The average thermocouple
1780 ! voltage is then stored on disk in the file name given above so that it
1790 ! can be used again.
1800   BEEP
1810   INPUT "GIVE A NAME FOR FILE TO HOLD PLOTTING DATA:",Plot_d$
1820   CREATE BDAT Plot_d$,10
1830   ASSIGN @Filep TO Plot_d$
1840   OUTPUT 709;"TD"
1850   ENTER 709:Date$
1860   J=J+1
1870   IF Iov=1 THEN 1890
1880   PRINT USING "10X,""Data set number    = """,DD":J
1890   IF Iov=1 AND J>1 THEN 1910
1900   PRINT USING "10X,""Month, date and time: """,14A":Date$
1910   IF Im=1 THEN
1920   BEEP
1930   INPUT "ENTER RPM",Rpm
1940   BEEP
1950   INPUT "ENTER ROTAMETER READING",Rota
1960   OUTPUT 709;"AR AF40 AL51 VR1"
1970   FOR I=0 TO 11
1980   Emf(I)=0
1990   OUTPUT 709;"AS SA"
2000   E=0
2010   FOR L=0 TO 19
2020   ENTER 709:E
2030   Emf(I)=Emf(I)+ABS(E)
2040   NEXT L
2050   Emf(I)=Emf(I)/20
2060   NEXT I
2070   OUTPUT @File;Rpm,Rota,Emf(*)
2080   ELSE
2090   BEEP
2100   ENTER @File;Rpm,Rota,Emf(*)
2110   END IF
2120   IF Iov=2 OR J=1 THEN
2130   PRINT USING "10X,""Rotor speed          = """,4D":Rpm
2140   PRINT USING "10X,""Rotameter reading   = """,DD.D":Rota
```

```
2150  END IF
2160  IF J=1 AND Iov=1 THEN
2170  PRINT
2180  PRINT USING "10X.""Data    Tci    Tco    Dcw    Ts    Tw    Dmax
      Q"""
2190  PRINT USING "10X.""Set #  (C)    (C)    (C)    (C)    (C)    (C)
      (W)"""
2200  END IF
2210  Jj=Jj+1
2220! 
2230! Determine bearing friction correction factor
2240  IF Rpm=700 THEN Qf=81
2250  IF Rpm=1400 THEN Qf=204
2260  IF Rpm=2800 THEN Qf=282
2270!
2280! Convert thermocouple voltage into temperature (C)
2290  FOR I=0 TO 11
2300  T(I)=0
2310  Emf(I)=ABS(Emf(I))
2320  FOR K=0 TO 9
2330   T(I)=T(I)+A(K)*Emf(I)^K
2340  NEXT K
2350  IF T(I)>99.99 THEN T(I)=99.99
2360!
2370! Call FUNCTION to apply thermocouple discrepancy
2380  T(I)=FNTbath(T(I),I)
2390  NEXT I
2400  Tci=T(10)
2410  Tco=T(11)
2420  IF Jj=1 AND Iov=2 THEN
2430  PRINT USING "10X.""Temperatures:"""
2440  PRINT USING "10X.""Ch #   40    41    42    43    44    45    46    47
      48    49"""
2450  PRINT USING "10X.""T (C) "".10(DD.DD.1X)";T(0),T(1),T(2),T(3),T(4),T(5),T(
      6),T(7),T(8),T(9)
2460  PRINT USING "10X.""Ch #   50    51"""
2470  PRINT USING "10X.""T (C) "".2(DD.DD.1X)";T(10),T(11)
2480  END IF
2490!
2500  Ts=(T(0)+T(9))/2            ! T IN VAPOR SPACE
2510  Tsum=0
2520  Nn=0
2530  FOR I=1 TO 8
2540  IF T(I)<100 AND T(I)>10 THEN
2550  Nn=Nn+1
2560  Tsum=Tsum+T(I)
2570  END IF
2580  NEXT I
2590  Twall=Tsum/Nn
2600  IF Iov=2 THEN
2610  PRINT
2620  PRINT USING "10X.""Coolant inlet temp (Tci)     "".DD.DD."" (C)""";Tci
2630  PRINT USING "10X.""Coolant outlet temp (Tco)    "".DD.DD."" (C)""";Tco
2640  PRINT USING "10X.""Coolant temp rise (Tco-Tci) = "".Z.DD."" (C)""";Tco-Tc
      i
2650  PRINT " "
2660  PRINT USING "10X.""Saturation temp (Ts)         "".DDD.DD."" (C)""";Ts
2670  PRINT USING "10X.""Average wall temp (Twall)    "".DDD.DD."" (C)""";Twall
2680  PRINT USING "10X.""Temp difference (Ts-Tci)    = "".DDD.DD."" (C)""";Ts-Tc
      i
2690  PRINT
```

```
2700  END IF
2710!
2720! Begin analysis
2730!
2740! Calculate density of cooling water
2750  Roh=1000.073818+.0273614*Tci-.006429147*Tci^2+.00002153167*Tci^3
2760!
2770! Calculate the mass flow rate of cooling water (MF)
2780  Mf=Roh*(6.3948461E-6+4.2553734E-6*Rota)
2790!
2800! Compute the average cooling box temperature
2810  Tavg=(Tci+Tco)/2
2820!
2830! Compute the average specific heat of water
2840  Cp=4221.790953-3.442282*Tavg+.08713516*Tavg^2-.0006781436*Tavg^3
2850!
2860! Compute the heat flux from the pipe
2870  Q=Mf*Cp*(Tco-Tci)-Qf
2880  IF Iov=2 THEN
2890  PRINT USING "10X,""Heat transfer rate           = "".4D.2D,"" (W)""""":Q
2900  PRINT
2910  END IF
2920  IF Iov=1 THEN
2930  PRINT USING "11X,DD,2X,6(3D.DD,2X),5D.DD";J,Tci,Tco,Tco-Tci,Ts,Twall,Ts-Tc
i,Q
2940  END IF
2950!
2960! Compute the Delta-T's used for plots
2970  Del_t=Ts-Tci
2980  Del_t2=Ts-Twall
2990  Del_t3=Twall-Tavg
3000  Del_t4=Tco-Tci
3010!
3020! Store plotting information on disk
3030  OUTPUT @Filep;Q,Del_t.Del_t2.Del_t3.Del_t4
3040  IF Im=1 THEN
3050  BEEP
3060  INPUT "WILL THERE BE ANOTHER DATA RUN? (1=YES, 0=NO)".Go_on
3070  BEEP
3080  IF Go_on=1 THEN INPUT "DO YOU WANT TEMPERATURES PRINTED THIS RUN? (1=YES,0
=NO)".Pr
3090     IF Pr=1 THEN Jj=0
3100     IF Go_on=1 THEN 1840
3110  ELSE
3120  IF Jj=5 THEN Jj=0
3130  IF J<Nrun THEN 1840
3140  END IF
3150  ASSIGN @File TO *
3160  ASSIGN @Filep TO *
3170  PRINT
3180  IF Im=1 THEN
3190  PRINT USING "10X,""NOTE: "".DD,"" data runs were stored in file "".10A":J,
D_file$
3200  ELSE
3210  PRINT USING "10X,""NOTE: Above analysis was performed for data in file "".
10A":D_file$
3220  END IF
3230  END
3240  DEF FNTbath(T,J)
3250!
```

```
3260! This function applies correction for thermocouples
3270!
3280   DIM A(2.2)
3290   DATA -1.8163682E-1,-1.5365448E-3,5.6154799E-5
3300   DATA -3.0304419E-1,5.8181952E-3,4.6818883E-5
3310   DATA -1.1301653E-1,-5.0517568E-3,1.11233041E-4
3320   READ A(0.0),A(0.1),A(0.2),A(1.0),A(1.1),A(1.2),A(2.0),A(2.1),A(2.2)
3330   IF J<10 THEN K=0
3340   IF J=10 THEN K=1
3350   IF J=11 THEN K=2
3360   D=A(K.0)
3370   FOR L=1 TO 2
3380   D=D+A(K.L)*T^L
3390   NEXT L
3400   T=T+D
3410   RETURN T
3420   FNEND
```

TABLE C.1

Results of Smooth Wall Condenser at 700 rpm

Month, date and time: 11:21:09:25:01
Rotor speed = 700
Rotameter reading = 40.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	20.38	21.51	1.13	65.38	23.71	45.00	752.48
2	20.37	21.57	1.20	65.56	23.93	45.19	800.03
3	20.37	21.50	1.13	65.61	23.86	45.24	755.64
4	20.43	22.57	2.14	89.64	27.18	69.22	1498.49
5	20.43	22.54	2.11	90.02	27.14	69.59	1474.16
6	20.45	22.53	2.08	90.46	27.14	70.01	1454.56
7	20.47	23.12	2.65	100.22	28.42	79.75	1874.76
8	20.47	23.11	2.64	100.20	28.49	79.72	1865.62
9	20.48	23.11	2.63	100.22	28.40	79.74	1855.23
10	20.49	22.63	2.14	89.99	27.02	69.50	1496.07
11	20.49	22.61	2.12	90.13	27.00	69.64	1482.75
12	20.48	22.66	2.18	90.17	26.99	69.70	1524.17
13	20.50	22.05	1.55	81.04	25.24	60.53	1061.29
14	20.49	22.13	1.64	81.13	25.42	60.64	1127.05
15	20.51	22.14	1.63	80.36	25.41	59.86	1123.89
16	20.52	21.84	1.32	77.68	24.17	57.16	890.19
17	20.50	21.84	1.35	77.66	24.12	57.16	911.67
18	20.52	21.83	1.31	77.68	24.24	57.16	887.14
19	20.50	21.55	1.05	69.60	23.13	49.09	693.72
20	20.51	21.55	1.04	69.64	23.22	49.13	685.15
21	20.51	21.56	1.05	69.81	23.11	49.30	693.09

NOTE: Above analysis was performed for data in file SMP_1C

where;

Dcw = Ts - Tci

Dmax = Tco - Tci

84

TABLE C.2

Results of Smooth Wall Condenser at 1400 rpm

Month, date and time: 11:21:09:45:55
Rotor speed   = 1400
Rotameter reading   = 40.0

Data Set #	T_{ci} (C)	T_{co} (C)	D_{cw} (C)	T_s (C)	T_w (C)	D_{max} (C)	Q (W)
1	20.51	21.65	1.14	58.45	24.10	37.94	633.97
2	20.51	21.70	1.19	58.58	24.25	38.07	672.92
3	20.52	21.67	1.15	58.43	24.14	37.91	643.02
4	20.50	22.42	1.92	67.97	26.73	47.37	1210.13
5	20.53	22.38	1.86	67.76	26.77	47.24	1166.14
6	20.52	22.40	1.87	67.92	26.78	47.40	1175.27
7	20.51	22.51	1.99	71.16	27.39	50.65	1264.11
8	20.52	22.49	1.97	71.18	27.46	50.66	1245.81
9	20.52	22.75	2.23	71.22	27.51	50.70	1439.03
10	20.52	22.68	2.16	71.17	27.44	50.65	1386.17
11	20.52	22.57	2.15	71.18	27.48	50.66	1378.27
12	20.51	23.53	3.02	82.69	29.21	62.18	2020.25
13	20.51	23.59	3.08	82.89	29.17	62.38	2066.95
14	20.51	23.53	3.02	82.76	29.23	62.25	2022.70
15	20.52	24.07	3.55	90.76	30.67	70.23	2410.14
16	20.52	24.10	3.58	91.00	30.73	70.48	2434.37
17	20.52	23.99	3.47	91.08	30.59	70.55	2353.12
18	20.52	24.55	4.03	96.50	31.97	75.98	2767.10
19	20.51	24.67	4.16	96.70	31.96	76.19	2860.52
20	20.52	24.86	4.34	96.63	31.88	76.11	2994.81
21	20.52	24.70	4.18	96.58	32.04	76.06	2876.14
22	20.51	24.14	3.63	88.46	30.37	67.96	2474.54
23	20.51	23.94	3.43	88.50	30.51	67.99	2322.97
24	20.50	24.14	3.64	88.57	30.45	68.07	2479.48
25	20.50	23.16	2.66	77.94	28.47	57.43	1756.31
26	20.51	23.14	2.63	77.96	28.49	57.35	1736.81
27	20.49	22.84	2.35	77.88	28.54	57.39	1528.63
28	20.52	22.03	1.51	66.11	25.68	45.59	910.78
29	20.51	21.98	1.46	65.99	25.29	45.48	874.94
30	20.50	22.01	1.50	65.96	25.66	45.46	904.92

NOTE: Above analysis was performed for data in file SMP_2

TABLE C.3

Results of Smooth Wall Condenser at 2800 rpm

Month. date and time: 11:21:09:48:30
Rotor speed   = 2800
Rotameter reading   = 40.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	20.51	21.88	1.37	50.21	24.64	29.70	727.59
2	20.50	21.91	1.41	50.11	24.61	29.61	756.26
3	20.50	21.85	1.35	50.08	24.66	29.58	711.26
4	20.54	22.45	1.91	58.27	26.69	37.73	1123.24
5	20.55	22.51	1.96	58.20	26.73	37.66	1164.54
6	20.55	22.47	1.92	58.21	26.70	37.65	1131.05
7	20.57	23.10	2.53	62.25	28.18	41.68	1583.53
8	20.57	22.92	2.35	62.23	28.24	41.66	1451.75
9	20.59	23.17	2.57	62.27	28.17	41.68	1613.65
10	20.60	23.90	3.30	69.79	29.77	49.19	2146.95
11	20.62	23.84	3.22	69.86	29.81	49.24	2090.97
12	20.61	23.80	3.20	69.70	29.74	49.09	2072.91
13	20.63	24.78	4.15	79.25	32.18	58.62	2779.30
14	20.63	24.83	4.20	79.59	32.44	58.96	2813.25
15	20.63	24.87	4.24	79.61	32.52	58.98	2841.10
16	20.67	25.45	4.78	86.41	35.19	65.73	3239.38
17	20.66	25.45	4.79	86.53	34.89	65.87	3248.62
18	20.63	25.70	5.07	86.53	34.88	65.90	3451.58
19	20.56	24.10	3.44	70.95	30.28	50.29	2250.60
20	20.67	23.90	3.23	69.80	30.10	49.13	2098.93
21	20.67	23.95	3.28	69.23	30.03	49.55	2132.85
22	20.69	27.66	6.97	97.13	38.39	76.43	4852.56
23	20.68	27.67	6.98	97.08	38.59	76:40	4863.03
24	20.69	27.43	6.74	97.05	38.21	76.37	4683.31
25	20.70	26.78	6.08	93.20	37.12	72.50	4137.47
26	20.70	26.77	6.07	92.97	37.13	72.27	4191.43
27	20.69	26.55	5.86	92.99	37.13	72.30	4033.87
28	20.68	25.17	4.49	84.54	34.49	63.86	3025.65
29	20.68	25.30	4.62	84.46	34.36	63.77	3121.90
30	20.70	25.19	4.49	84.47	34.45	63.77	3029.08

NOTE: Above analysis was performed for data in file SMP_3

TABLE C.4

Results of Straight 22 Fin Condenser at 700 rpm

Month, date and time: 11:21:09:58:27
Rotor speed = 700
Rotameter reading = 35.0

Data Set #	T_{ci} (C)	T_{co} (C)	D_{cw} (C)	T_s (C)	T_w (C)	D_{max} (C)	Q (W)
1	21.24	22.87	1.63	35.16	27.59	13.92	973.95
2	21.24	22.89	1.63	35.06	27.52	13.82	977.16
3	21.23	22.89	1.65	35.18	27.59	13.95	991.11
4	21.25	24.10	2.85	52.48	33.85	31.23	1768.00
5	21.24	24.01	2.76	52.37	33.79	31.13	1710.48
6	21.25	24.13	2.88	52.28	33.74	31.03	1782.91
7	21.25	25.56	4.32	76.26	40.32	55.01	2715.33
8	21.26	25.59	4.33	76.34	40.42	55.09	2726.95
9	21.26	25.54	4.28	76.44	40.59	55.19	2694.50
10	21.25	27.14	5.88	99.37	45.38	78.12	3732.05
11	21.25	27.17	5.92	99.34	45.57	78.09	3754.90
12	21.26	27.21	5.96	99.37	45.24	78.12	3778.17
13	21.25	25.22	4.98	88.19	43.05	66.94	3232.72
14	21.25	26.08	4.83	88.06	42.53	66.81	3049.72
15	21.25	26.17	4.93	88.14	42.48	66.89	3110.36
16	21.24	24.33	3.10	55.41	34.84	34.18	1924.83
17	21.24	24.48	3.24	55.51	34.92	34.27	2016.45
18	21.24	24.31	3.08	55.44	35.00	34.21	1912.04
19	21.24	23.04	1.80	38.66	28.69	17.42	1087.22
20	21.25	23.18	1.93	38.62	28.68	17.37	1170.99
21	21.25	23.16	1.91	38.65	28.66	17.40	1159.25

NOTE: Above analysis was performed for data in file S22FP_1

TABLE C.5

Results of Straight 22 Fin Condenser at 1400 rpm

Month, date and time: 11:21:10:00:51
Rotor speed   = 1400
Rotameter reading   = 35.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	21.23	22.69	1.46	31.28	26.76	10.05	743.09
2	21.23	22.55	1.32	30.34	26.29	9.11	652.27
3	21.24	22.57	1.33	31.14	26.65	9.90	658.61
4	21.24	23.78	2.54	40.18	30.70	18.95	1442.46
5	21.23	23.73	2.50	40.15	30.80	18.92	1414.20
6	21.23	23.73	2.50	40.16	30.74	18.93	1417.43
7	21.23	25.53	4.30	52.79	36.67	31.57	2585.12
8	21.22	25.46	4.23	52.88	36.67	31.66	2539.92
9	21.23	25.53	4.30	52.91	36.64	31.68	2585.10
10	21.21	27.56	6.36	64.87	42.13	43.66	3915.68
11	21.21	27.07	5.85	64.78	42.20	43.57	3588.84
12	21.21	27.04	5.83	64.84	42.16	43.63	3575.67
13	21.20	28.93	7.73	76.19	47.40	54.99	4806.66
14	21.20	28.90	7.70	76.27	47.25	55.07	4783.38
15	21.20	28.65	7.45	76.34	47.31	55.14	4623.57
16	21.18	26.97	5.79	69.10	43.18	47.92	4064.17
17	21.17	27.38	6.21	69.00	43.18	47.82	4372.52
18	21.19	27.41	6.22	68.89	43.20	47.70	4381.32
19	21.17	27.01	5.85	66.77	42.08	45.60	4102.39
20	21.15	27.01	5.86	66.77	42.05	45.62	4112.27
21	21.16	26.89	5.73	66.72	42.07	45.56	4017.43
22	21.14	25.70	4.57	57.38	37.86	36.25	3161.11
23	21.14	25.65	4.51	57.36	37.92	36.22	3119.40
24	21.15	25.64	4.48	57.14	37.83	35.99	3100.46
25	21.15	24.24	3.09	46.76	33.05	25.62	2074.46
26	21.15	24.29	3.14	46.45	33.02	25.30	2110.22
27	21.15	24.34	3.19	46.34	33.10	25.20	2146.58

NOTE: Above analysis was performed for data in file S22FP_2

TABLE C.6

Results of Straight 22 Fin Condenser at 2800 rpm

Month, date and time: 11:21:10:03:09
Rotor speed = 2800
Rotameter reading = 40.0

Data Set #	T_{ci} (C)	T_{co} (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	21.16	22.57	1.41	29.89	26.54	8.73	835.12
2	21.16	22.57	1.42	29.98	26.62	8.82	762.63
3	21.15	22.61	1.45	29.99	26.60	8.84	788.78
4	21.14	23.54	2.40	35.40	29.48	14.26	1482.87
5	21.15	23.60	2.45	35.42	29.48	14.28	1524.71
6	21.14	23.58	2.44	35.33	29.43	14.18	1515.63
7	21.09	24.87	3.78	43.63	33.85	22.54	2502.83
8	21.09	25.09	4.00	44.48	33.96	23.39	2666.91
9	21.11	25.08	3.97	43.56	33.93	22.56	2643.71
10	21.09	26.40	5.31	52.30	38.69	31.71	3632.39
11	21.09	26.49	5.40	51.42	38.51	30.33	3698.22
12	21.09	26.60	5.51	52.13	38.70	31.09	3777.92
13	21.11	28.58	7.47	62.98	44.37	41.76	5220.80
14	21.11	28.66	7.55	62.91	44.22	41.79	5278.50
15	21.13	28.56	7.43	62.89	44.27	41.76	5191.06
16	21.13	27.67	6.54	58.05	41.65	36.92	4538.75
17	21.10	27.70	6.59	58.07	41.71	36.97	4576.45
18	21.12	27.62	6.50	58.18	41.62	37.06	4509.38
19	21.10	26.78	5.69	53.21	38.83	32.12	3906.45
20	21.09	26.62	5.53	53.57	39.15	32.48	3795.44
21	21.07	26.68	5.61	53.59	39.22	32.51	3849.99
22	21.11	24.35	3.24	40.17	31.93	19.06	2104.07
23	21.11	24.42	3.31	40.14	31.90	19.04	2159.86
24	21.11	24.31	3.20	40.17	31.90	19.06	2078.68

NOTE: Above analysis was performed for data in file S22FP_3

TABLE C.7

Results of Helical 16 Fin Condenser at 700 rpm

Month, date and time: 11:21:10:54:06
Rotor speed = 700
Rotameter reading = 40.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	21.18	26.44	5.26	92.47	43.99	61.29	3791.12
2	21.19	26.15	4.97	81.52	43.65	60.43	3577.23
3	21.19	26.30	5.11	80.34	43.58	59.15	3681.68
4	21.24	27.54	6.30	100.22	51.01	78.98	4562.72
5	21.25	27.49	6.24	100.22	51.11	78.97	4515.00
6	21.25	27.41	6.16	100.22	51.33	78.97	4454.02
7	21.28	27.33	6.05	92.57	47.10	71.40	4375.26
8	21.29	27.05	5.77	92.74	47.03	71.46	4171.29
9	21.27	27.17	5.90	92.55	46.99	71.38	4263.09
10	21.31	26.06	4.76	72.21	41.39	50.91	3424.10
11	21.31	25.95	4.64	72.06	40.95	50.75	3340.65
12	21.31	25.88	4.57	71.93	40.34	50.62	3288.09
13	21.33	24.79	3.45	58.51	36.41	37.29	2471.79
14	21.33	24.88	3.56	58.44	36.32	37.11	2538.37
15	21.33	24.77	3.44	58.45	36.26	37.12	2454.83
16	21.39	23.80	2.41	48.57	32.07	27.19	1697.40
17	21.39	23.73	2.34	48.97	32.08	27.58	1642.79
18	21.39	23.73	2.34	48.52	31.59	27.23	1639.71
19	21.40	22.99	1.59	42.10	29.06	20.70	1092.89
20	21.39	23.03	1.64	42.02	29.07	20.62	1125.11
21	21.40	23.04	1.55	42.28	29.22	20.88	1133.60
22	21.41	24.68	3.27	57.00	35.94	35.59	2327.39
23	21.41	24.49	3.08	57.43	36.10	36.02	2186.27
24	21.41	24.65	3.24	57.62	36.14	36.21	2307.99
25	21.44	25.74	4.29	69.07	40.50	47.63	3092.19
26	21.44	25.46	4.01	69.15	40.45	47.70	2875.96
27	21.43	25.75	4.31	63.05	40.43	47.52	3097.39

NOTE: Above analysis was performed for data in file H16FP_1

90

TABLE C.8

Results of Helical 16-Fin Condenser at 1400 rpm

Month, date and time: 11:21:10:59:43
Rotor speed   = 1400
Rotameter reading   = 40.0

Data Set #	T_{ci} (C)	T_{co} (C)	D_{cw} (C)	T_s (C)	T_w (C)	D_{max} (C)	q (W)
1	21.44	23.10	1.67	38.79	29.40	17.35	1022.99
2	21.44	23.11	1.67	38.79	29.40	17.35	1023.59
3	21.44	24.05	2.61	46.29	33.22	24.85	1719.39
4	21.45	24.00	2.56	46.31	32.93	24.86	1678.73
5	21.45	24.03	2.58	46.32	33.16	24.87	1696.93
6	21.46	25.28	3.81	56.46	37.81	35.00	2606.34
7	21.47	25.24	3.77	56.58	37.96	35.11	2574.79
8	21.47	25.23	3.76	56.25	37.85	34.79	2569.39
9	21.48	26.82	5.34	68.82	43.76	47.34	3729.47
10	21.48	26.83	5.36	69.79	43.77	47.31	3740.94
11	21.47	26.75	5.28	68.80	43.76	47.32	3685.49
12	21.49	28.52	7.03	83.70	50.38	62.21	4974.59
13	21.49	28.48	6.99	83.83	50.51	62.34	4946.35
14	21.50	28.53	7.03	83.91	50.34	62.31	4973.88
15	21.50	29.21	7.72	90.23	52.50	68.73	5481.07
16	21.49	26.14	4.65	62.47	40.75	40.98	3219.08
17	21.49	26.03	4.54	62.46	40.65	40.97	315.91
18	21.49	26.03	4.54	62.36	40.64	40.97	3141.81
19	21.49	27.75	6.25	77.42	47.57	55.93	4402.34
20	21.50	27.77	6.28	77.47	47.57	55.98	4420.37
21	21.50	27.82	6.33	77.54	47.61	55.04	4456.53
22	21.48	24.85	3.36	53.19	36.14	31.71	2274.51
23	21.49	24.86	3.37	53.25	36.38	31.77	2278.69
24	21.49	24.82	3.33	53.37	36.29	31.98	2250.95

NOTE: Above analysis was performed for data in file H16FF_2

TABLE C.9

Results of Helical 16 Fin Condenser at 2800 rpm

```
Month, date and time: 11:21:11:02:12
Rotor speed          = 2800
Rotameter reading    = 40.0
```

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Qmax (C)	Q (W)
1	21.43	23.21	1.78	37.28	30.02	15.85	1028.22
2	21.43	23.18	1.75	37.26	30.00	15.82	1008.18
3	21.43	23.18	1.75	37.35	30.06	15.92	1004.56
4	21.42	24.07	2.65	42.71	33.02	21.29	1669.46
5	21.41	24.10	2.69	42.73	32.98	21.32	1702.94
6	21.41	24.06	2.65	42.72	32.97	21.31	1670.76
7	21.37	25.33	3.96	51.45	37.60	30.08	2638.90
8	21.37	25.34	3.97	51.59	37.62	30.23	2641.96
9	21.37	25.36	3.99	51.63	37.93	30.26	2660.08
10	21.39	27.00	5.61	61.69	43.48	40.30	3848.71
11	21.39	27.04	5.65	61.54	43.29	40.15	3877.14
12	21.39	27.01	5.62	61.51	43.36	40.12	3858.40
13	21.45	28.92	7.47	73.43	49.23	51.98	5220.95
14	21.45	28.87	7.42	73.33	49.26	51.88	5180.00
15	21.45	28.33	7.38	73.25	49.32	51.80	5153.57
16	21.46	29.30	7.84	77.68	51.50	56.21	5493.81
17	21.46	29.68	8.22	79.19	52.33	57.73	5772.10
18	21.44	28.23	6.79	68.70	46.79	47.26	4719.09
19	21.46	28.19	6.73	68.37	46.62	46.92	4677.32
20	21.46	28.26	6.80	68.99	47.00	47.53	4727.27
21	21.43	26.09	4.66	55.36	39.76	33.93	3152.15
22	21.43	26.08	4.65	55.39	39.73	33.96	3147.29
23	21.41	26.06	4.65	55.38	39.73	33.97	3143.90
24	21.44	24.68	3.24	46.04	34.44	24.61	2105.56
25	21.44	24.71	3.29	45.86	34.41	24.43	2134.03
26	21.45	24.71	3.27	46.06	34.45	24.61	2126.56

NOTE: Above analysis was performed for data in file H16FP_2

92

TABLE C.10

Results of Helical 14 Fin Condenser at 700 rpm

Month, date and time: 11:21:10:08:33
Rotor speed   = 700
Rotameter reading = 43.0

Data Set #	T_{ci} (C)	T_{co} (C)	D_{cw} (C)	T_s (C)	T_w (C)	D_{max} (C)	Q (W)
1	21.38	22.18	.79	33.41	25.37	12.02	547.14
2	21.38	22.12	.74	32.67	25.11	11.29	502.83
3	21.38	22.12	.75	32.97	25.17	11.59	509.39
4	21.39	23.01	1.62	43.22	29.29	21.83	1259.56
5	21.38	23.08	1.70	43.30	29.19	21.91	1319.48
6	21.40	23.12	1.72	43.47	29.35	22.08	1340.45
7	21.40	23.93	2.53	52.17	32.98	30.77	1959.71
8	21.40	23.96	2.56	51.85	33.00	30.45	1983.65
9	21.41	23.93	2.53	52.04	32.32	30.64	1959.69
10	21.39	24.78	3.38	61.63	36.96	40.24	2410.54
11	21.41	24.67	3.26	61.56	36.94	40.15	2320.78
12	21.41	24.77	3.36	61.62	36.82	40.21	2394.61
13	21.46	26.27	4.82	72.78	41.57	51.32	3552.44
14	21.45	26.10	4.65	72.81	41.60	51.36	3428.84
15	21.45	26.10	4.65	72.95	41.68	51.49	3385.01
16	21.48	27.20	5.72	91.54	46.32	70.06	4336.15
17	21.48	27.23	5.76	91.10	46.28	69.62	4365.87
18	21.48	27.15	5.67	91.57	47.03	70.08	4195.61
19	21.52	26.79	5.27	92.24	46.30	70.72	3895.43
20	21.52	26.69	5.16	92.32	46.34	70.79	3860.87
21	21.53	26.77	5.24	92.01	46.15	70.48	3966.10
22	21.51	25.68	4.17	67.66	39.50	46.15	3098.58
23	21.50	25.77	4.28	67.48	39.50	45.98	3238.38
24	21.50	25.64	4.14	67.36	39.39	45.86	3119.26
25	21.53	24.31	2.78	53.80	34.04	32.26	2064.40
26	21.53	24.24	2.70	53.85	33.79	32.32	2007.87
27	21.52	24.26	2.74	54.40	33.83	32.88	2031.46
28	21.54	22.65	1.11	38.01	26.83	16.48	779.08
29	21.53	22.64	1.11	38.13	26.76	16.60	778.49
30	21.53	22.64	1.11	38.07	26.73	16.54	779.76

NOTE: Above analysis was performed for data in file H14FP_1

93

TABLE C.11

Results of Helical 14 Fin Condenser at 1400 rpm

Month, date and time: 11:21:10:23:14
Rotor speed   = 1400
Rotameter reading = 42.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	21.52	22.58	1.05	31.63	26.14	10.10	609.04
2	21.53	22.58	1.05	31.66	26.20	10.13	605.82
3	21.48	23.70	2.21	41.69	30.64	20.21	1505.33
4	21.51	23.68	2.18	41.62	30.60	20.11	1475.86
5	21.52	23.70	2.18	41.76	30.59	20.24	1478.32
6	21.44	24.90	3.46	52.10	35.29	30.66	2466.72
7	21.42	24.85	3.44	51.68	35.43	30.26	2451.16
8	21.43	24.85	3.42	51.86	35.22	30.43	2437.71
9	21.43	25.50	4.07	57.23	37.66	35.80	2939.35
10	21.44	25.65	4.21	56.95	38.06	35.51	3047.02
11	21.46	25.55	4.09	57.08	37.71	35.62	2958.06
12	21.52	27.22	5.70	70.97	43.92	49.45	4197.36
13	21.56	27.30	5.74	71.04	44.01	49.47	4229.64
14	21.54	27.25	5.71	71.11	43.90	49.57	4204.70
15	21.56	28.33	6.77	79.91	47.70	58.34	5021.05
16	21.57	28.35	6.78	79.93	47.83	58.37	5031.74
17	21.57	28.37	6.80	79.99	47.87	58.41	5044.23
18	21.50	26.34	4.84	62.94	40.57	41.44	3532.12
19	21.50	26.31	4.81	63.12	40.48	41.63	3511.86
20	21.51	26.42	4.90	63.30	40.58	41.78	3582.58
21	21.56	24.71	3.15	50.12	34.37	28.56	2198.27
22	21.58	24.68	3.10	50.16	34.26	28.58	2159.74
23	21.56	24.68	3.12	50.11	34.30	28.55	2180.74
24	21.60	23.20	1.59	37.50	28.72	15.90	1011.86

NOTE: Above analysis was performed for data in file H14FP_2C

TABLE C.12

Results of Helical 14-Fin Condenser at 2800 rpm

Month, date and time: 11:21:10:13:35
Rotor speed   = 2800
Rotameter reading   = 41.0

| Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	21.53	23.16	1.63	34.55	29.03	13.12	947.67
2	21.52	23.17	1.64	34.59	28.05	13.06	958.30
3	21.52	23.21	1.69	34.61	28.02	13.10	996.27
4	21.28	24.03	2.75	41.57	31.45	20.29	1796.15
5	21.30	23.97	2.67	41.55	31.44	20.26	1735.10
6	21.30	24.05	2.75	41.58	31.44	20.28	1791.59
7	21.51	25.50	3.99	48.53	35.42	27.01	2728.71
8	21.52	25.26	3.74	48.97	35.21	27.45	2538.46
9	21.47	25.23	3.77	48.73	35.30	27.26	2561.35
10	21.48	26.37	4.89	56.48	39.38	35.00	3407.45
11	21.47	26.35	4.88	56.93	39.59	35.46	3399.54
12	21.51	26.25	4.74	56.56	39.46	35.05	3296.36
13	21.60	27.92	6.32	65.70	44.07	44.10	4486.17
14	21.59	27.81	6.22	65.80	44.13	44.21	4408.57
15	21.61	27.91	6.30	65.96	44.18	44.35	4469.97
16	21.61	29.48	7.87	76.23	49.44	54.63	5654.60
17	21.62	29.25	7.63	75.32	49.60	54.70	5470.24
18	21.63	29.46	7.83	76.41	49.56	54.78	5625.34
19	21.45	27.45	6.00	62.56	42.28	41.11	4245.23
20	21.48	27.25	5.76	62.49	42.24	41.01	4066.89
21	21.45	27.29	5.84	62.43	42.15	40.98	4120.43
22	21.30	24.42	3.12	45.07	33.20	23.79	2074.61
23	21.32	24.56	3.24	45.11	33.31	23.79	2150.55
24	21.31	24.47	3.16	44.93	33.13	23.63	2103.05
25	21.71	23.16	1.45	24.81	27.94	13.10	796.17
26	21.75	23.26	1.51	34.83	27.96	13.08	860.74
27	21.66	23.27	1.61	34.86	27.98	13.20	932.94

NOTE: Above analysis was performed for data in file H14FP_3

95

END

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

TABLE C.13

Results of Helical 36 Fin Condenser at 700 rpm

Month, date and time: 10:20:16:33:43
Rotor speed   = 700
Rotameter reading   = 40.5

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	20.15	21.36	1.21	34.69	25.88	14.54	823.50
2	20.17	21.43	1.26	34.82	25.92	14.65	859.06
3	20.18	21.32	1.14	34.77	25.96	14.59	772.10
4	20.23	22.57	2.34	47.61	30.88	27.38	1644.98
5	20.23	22.26	2.03	47.82	31.04	27.59	1416.40
6	20.22	22.42	2.21	47.78	31.27	27.56	1546.00
7	20.30	23.20	2.90	59.94	35.24	39.63	2059.17
8	20.31	23.46	3.15	59.97	34.93	39.66	2241.21
9	20.31	23.12	2.81	60.03	34.81	39.72	1988.03
10	20.34	24.55	4.21	68.55	39.00	48.21	3020.64
11	20.36	24.32	3.95	68.59	39.00	48.22	2830.69
12	20.37	24.52	4.15	68.62	38.92	48.25	2976.65
13	20.40	23.69	3.29	66.02	36.30	45.62	2345.22
14	20.40	23.63	3.23	65.98	36.40	45.58	2299.15
15	20.40	23.79	3.39	66.03	36.17	45.63	2419.21
16	20.42	22.95	2.53	56.09	33.83	35.67	1785.97
17	20.42	23.03	2.62	55.93	33.75	35.52	1848.55
18	20.42	22.97	2.55	55.96	33.82	35.54	1798.09
19	20.42	22.34	1.92	40.87	28.89	20.45	1333.22
20	20.43	22.10	1.67	40.79	28.64	20.37	1150.71
21	20.41	22.12	1.71	40.59	28.72	20.18	1179.47
22	20.41	21.83	1.42	34.09	26.27	13.68	964.65
23	20.43	21.72	1.29	34.18	26.24	13.75	866.54
24	20.41	21.73	1.32	34.08	26.36	13.67	894.70

NOTE: Above analysis was performed for data in file H36FP_1

TABLE C.14

Results of Helical 36-Fin Condenser at 1400 rpm

```
Month, date and time: 10:20:16:39:58
Rotor speed          = 1400
Rotameter reading    = 40.0
```

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	20.41	21.81	1.40	31.46	26.04	11.05	827.06
2	20.44	21.77	1.33	31.33	26.07	10.88	778.15
3	20.44	21.80	1.36	31.17	26.10	10.73	795.18
4	20.45	22.90	2.45	41.32	30.90	20.86	1601.30
5	20.45	22.80	2.35	41.39	30.78	20.94	1530.27
6	20.45	22.85	2.40	41.30	30.69	20.85	1567.93
7	20.44	24.00	3.55	52.26	36.04	31.82	2414.64
8	20.44	23.87	3.43	52.30	35.91	31.86	2321.88
9	20.42	23.72	3.30	52.21	36.05	31.79	2227.51
10	20.43	24.92	4.49	64.22	41.60	43.79	3105.54
11	20.46	25.47	5.02	64.36	41.66	43.91	3492.50
12	20.45	25.16	4.71	64.57	41.56	44.12	3268.77
13	20.44	26.43	5.99	68.74	45.66	48.30	4208.36
14	20.46	26.23	5.77	68.89	45.72	48.43	4047.98
15	20.47	26.67	6.20	68.93	45.54	48.47	4365.67
16	20.46	24.98	4.53	61.55	40.83	41.10	3133.05
17	20.46	25.21	4.75	61.44	40.71	40.98	3297.64
18	20.47	25.50	5.03	61.47	40.67	41.01	3505.08
19	20.47	24.92	4.45	61.27	40.51	40.80	3078.39
20	20.48	23.60	3.12	48.25	34.30	27.77	2098.22
21	20.51	23.42	2.91	48.36	34.40	27.85	1941.98
22	20.47	23.47	3.00	48.29	34.28	27.81	2006.05
23	20.51	22.38	1.87	35.10	27.84	14.60	1177.25
24	20.47	22.32	1.85	35.11	27.83	14.64	1158.71
25	20.49	22.33	1.84	35.02	27.86	14.53	1153.65

NOTE: Above analysis was performed for data in file 436FP_2

97.

TABLE C.15

Results of Helical 36 Fin Condenser at 2800 rpm

Month, date and time: 10:20:16:43:43
Rotor speed   = 2800
Rotameter reading   = 40.0

Data Set #	Tci (C)	Tco (C)	Dcw (C)	Ts (C)	Tw (C)	Dmax (C)	Q (W)
1	20.50	22.05	1.55	29.80	26.52	9.30	857.87
2	20.53	21.88	1.35	29.79	26.48	9.26	716.51
3	20.51	22.26	1.74	29.78	26.46	9.27	1003.73
4	20.52	22.92	2.39	34.91	29.71	14.39	1480.71
5	20.52	23.29	2.76	34.92	29.72	14.39	1755.82
6	20.51	22.80	2.29	35.03	29.91	14.52	1402.44
7	20.51	24.06	3.55	42.99	34.43	22.48	2337.12
8	20.51	23.84	3.33	43.21	34.20	22.70	2169.10
9	20.49	24.22	3.73	42.41	34.32	21.92	2465.21
10	20.52	25.67	5.15	51.24	39.73	30.73	3511.70
11	20.51	25.71	5.19	51.05	39.68	30.54	3544.39
12	20.49	25.81	5.32	51.16	39.85	30.67	3637.20
13	20.54	27.73	7.20	62.05	46.19	41.51	5019.56
14	20.51	27.71	7.20	61.94	46.25	41.43	5022.39
15	20.50	27.76	7.26	62.14	46.28	41.65	5067.25
16	20.42	25.18	4.76	48.00	37.72	27.58	3227.41
17	20.43	25.18	4.75	48.02	37.81	27.59	3215.78
18	20.41	25.24	4.83	48.13	37.59	27.72	3277.74
19	20.41	25.24	4.83	48.58	38.33	28.17	3277.19
20	20.41	25.14	4.74	48.51	38.19	28.10	3209.41
21	20.35	25.42	5.07	49.93	38.99	29.57	3452.12
22	20.37	25.27	4.90	49.86	38.69	29.49	3325.45
23	20.37	25.33	4.96	49.89	38.93	29.52	3375.67
24	20.42	27.05	6.63	57.73	43.99	37.31	4601.58
25	20.37	26.92	6.55	57.74	43.75	37.37	4543.17
26	20.38	27.04	6.66	57.53	43.74	37.15	4622.10
27	20.43	22.50	2.07	31.69	27.45	11.26	1240.32
28	20.46	22.40	1.95	31.62	27.37	11.17	1152.56
29	20.46	22.42	1.96	31.64	27.34	11.18	1165.32

NOTE: Above analysis was performed for data in file H36FP_3

LIST OF REFERENCES

1. Daley, T. J., <u>The Experimental Design and Operation of a Wickless Heat Pipe</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, June 1970.

2. Newton, W. H., <u>Performance Characteristic of Rotating Non-capillary Heat Pipes</u>, M. S. Thesis, Naval Post-graduate School, Monterey, California, June 1971.

3. Woodard, J. S., <u>The Operation of Rotating Non-capillary Heat Pipes</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, March 1972.

4. Schafer, C. E., <u>Augmenting the Heat Transfer Performance of Rotating, Two-Phase Thermosyphons</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, September 1974.

5. Tucker, J. L., <u>Design Improvements on a Rotating Heat Pipe Apparatus</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, September 1976.

6. Loynes, J. L., <u>Design Improvements on a Rotating Heat Pipe Apparatus</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, September 1976.

7. Wagenseil, L. L., <u>Heat Transfer Performance of Rotating Heat Pipes</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, September 1976.

8. Tantrakul, C., <u>Condensation Heat Transfer Inside Rotating Heat Pipes</u>, M. S. and Engineer's Theses, Naval Postgraduate School, Monterey, California, June 1977.

9. Weigel, H. J., <u>Heat Transfer Performance of a Rotating Heat Pipe Using Different Condensers and Working Fluids</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, June 1979.

10. Gardner, G. H., <u>An Experimental Evaluation of the Thermal Performance of a Rotating Heat Pipe with Internal Axial Fins</u>, M. S. Thesis, Naval Postgraduate School, Monterey, California, June 1983.

11. Leppert, G., and Nimmo, B., "Laminar Film Condensation on Surfaces Normal to Body or Internal Forces," Transactions of the ASME, p. 178, February 1968.

12. Nimmo, B..G., and Leppert, G., "Laminar Film Condensation on Finite Horizontal Surface," Clarckson College of Technology, Dotsdam, New York, 1970.

13. Roetzel, W., and Neuman, M., "Uniform Heat Flux in a Paper Drying Drum with a Non-Cylindrical Condensation Surface Operating Under Rimming Conditions," Council for Scientific and Industrial Research, Pretoria, South Africa, March 1974.

14. Nicol, A. A., and Gacesa, M., "Condensation of Steam on a Rotating Vertical Cylinder," ASME Paper No. 69-HT-36. (1969)

15. Kline, S. J., and McClintock, F. A., "Describing Uncertainties in Single Sample Experiments," Mechanical Engineering p.3, January 1953.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	2
2.	Library, Code 0142 Naval Postgraduate School Monterey, California 93943	2
3.	Department Chairman, Code 69 Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943	1
4.	Professor P. J. Marto, Code 69Mx Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943	5
5.	Dr. A. S. Wanniarachchi, Code 69 Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943	1
6.	Dz. K. Komutanliği Okullar ve Kurslar Dairesi Bakanliklar, Ankara, Turkey	5
7.	Deniz Harp Okulu Kütüphanesi Heybeliada, İstanbul Turkey	1
8.	İstanbul Teknik Üniversitiesi Kütüphanesi İstanbul, Turkey	1
9.	Boğazici Üniversitesi Kütüphanesi Istanbul, Turkey	1

10. Orta Doğu Teknik Universitesi   1
    Kütüphanesi
    Ankara, Turkey

11. Adnan Nefesoğlu   3
    Attar Sokak 15/11
    Gazi Osman Paşa
    Ankara, Turkey

FILME